

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 23\_UHF-0-0-2/033\_

Rev.: D 

### Description

Straight panel receptacle jack, flange mount

Interface standards  
IEC 60169-12



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 0.2 GHz

#### Mechanical Data

Weight 0.0233 kg

#### Environmental Data

Operating Temperature -55 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

|                |            |
|----------------|------------|
| Centre contact | Brass      |
| Outer contact  | Brass      |
| Body           | Brass      |
| Insulator      | PFA / PTFE |

##### Surface Plating

Silver Plating  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00010048

#### Ordering Information

Single package 23\_UHF-0-0-2/033\_E

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**