

Semi-Rigid Coaxial Cable

MECHANICAL CHARACTERISTICS

Outer Conductor Diameter, inch (mm)	0.141 + 0.003/ 0.002 (3.581 + 0.076 / -0.051)
Dielectric Diameter, inch (mm)	0.118 (2.997)
Center Conductor Diameter, inch (mm)	0.040 +/- 0.001 (1.016 +/- 0.025)
Maximum Length, feet (meters)	20 (6.1)
Minimum Inside Bend Radius, inch (mm)	0.5 (12.7)
Weight, pounds/100 ft. (kg/100 meters)	3.2 (4.76)

ELECTRICAL CHARACTERISTICS

Impedance, ohms	50		
Frequency Range GHz	DC-36		
Velocity of Propagation %			
Capacitance, pF/ft. (pF/meter)	26.6 (87.3)		
Typical Insertion Loss, dB/ft. (dB/meter) and Average Power Handling, Watts CW at 20 degrees Celsius and Sea level	Frequency	Insertion Loss	Power
	0.5 GHz	0.08 (0.26)	692.1
	1.0 GHz	0.10 (0.33)	486.8
	5.0 GHz	0.23 (0.76)	213
	10.0 GHz	0.33 (1.09)	148.2
20.0 GHz	0.48 (1.58)	102.5	
Corona Extinction Voltage, VRMS @ 60 Hz	1900		
Voltage Withstand, VRMS @ 60 Hz	5000		

ENVIRONMENTAL CHARACTERISTICS

Outer Conductor Integrity Temperature, Deg Celsius	Not Applicable
Maximum Operating Temperature, Deg Celsius	225

MATERIALS

Outer Conductor	TIN-PLATED COPPER
Dielectric	LD PTFE
Center Conductor	SPC

CUTAWAY

